

Bestway

3.96m x 84cm
13' x 33"
FAST SET™

84cm
33"

80%
7,340 L
1,939 gal.

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (lmp 20 test): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type d'agent de filtration: filtre à cartouche synthétique
Efficacité de réduction de turbidité TBR (%) 50%
Masse retenue en g (test DP 20): 20g
Valeur de nettoyage limite: nettoyez la cartouche tous les jours, remplacez-la lorsque que le débit chute en dessous de 400 gal/h (1,514 L/h)
Débit nominal:
• Débit d'eau de la pompe (capacité de la pompe): 2,006 L/h (530 gal./h, 2,0 m³/h)
• Débit d'eau du système de piscine intégré (débit du système): 1,817 L/h (480 gal./h, 1,5 m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Art des filtres médias: Cartridgefilter aus Kunststoff
Effizienz bei der Trübungreduktion TBR (%): 50%
Zurückgehaltene Masse in g (DP 20 Test): 20g
Reinigungswert: Reinigen Sie das Filtermedium täglich, ersetzen Sie das Kartusche, wenn der Durchflussrate auf 400 Gal./h (1,514 L/h) sinkt.
Nennleistung Durchflussrate:
• Wasserdurchflussrate der Pumpe (Pumpenkapazität): 2,006 L/h (530 gal./h, 2,0 m³/h)
• Wasserdurchflussrate des integrierten Pool-Systems (System-Durchflussrate): 1,817 L/h (480 gal./h, 1,5 m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Type of filter medium: synthetic cartridge filter
Turbidity reduction efficiency TBR (%) 50%
Retained mass in g (test DP 20): 20g
Limit clean value: Clean the cartridge every day, replace the cartridge when flow rate fall down to 400gal/h (1,514L/h)
Nominal flow rate:
• Pump's water flow rate (pump capacity): 2,006L/h (530gal./h, 2.0m³/h)
• Integrated pool system water flow rate (system flow rate): 1,817L/h (480gal./h, 1.5m³/h)

Dimensions-Capacités
Abmessungen-Fassungsvermögen
Dimensioni-Capacità
Amfeningen-Inhoud
Dimensiones-Capacidades
Dimensjoner-Kapacitet
ΔΙΑΣΤΑΣΕΙΣ-ΧΩΡΗΚΙΟΤΗΤΑ
Размеры-Вместимость
Rozmery-Objemy
Mål-Kapacitet
Storlek-Kapacitet
Mittat-tilavuus

Rozmery-Kapacita
Wymiary-Wydajność
Dimensziókapacitások
Izméri-teljesítmény
Måttipsen-føljes
Dimensiones-Capacidades
Dimensjoner-Kapacitet
Dimensji-Capacità
Размеры-Вместимость
Rozmery-Objemy
Mål-Kapacitet
Storlek-Kapacitet
Mittat-tilavuus

80%
7,340 L
1,939 gal.

Aboveground swimming pool kit
Kit piscine à poser sur le sol
Bausatz für auf dem Boden aufgestelltes Schwimmbecken
Kit piscina fuori terra
Kit voor bovengronds zwembad
Kit de piscina elevada
Svømmebassinsæt til placering på jorden
KIT de piscina superior ao solo
KIT ΠΙΣΙΝΑΣ ΕΠΙΦΑΝΕΙΑΣ
Наземный плавательный бассейн в комплекте
Sada nadzemního bazénu
Svømmebassingsæt til bruk over bakken
Utstrusting for pool ovan mark

Contents: One pool, filter pump, repair patch
Contenus: Une piscine, une pompe de filtration, une rustine
Inhalt: Ein Pool, eine Filterpumpe, Reparaturflicken
Contenuto: Una piscina, una pompa a filtro, toppa di riparazione
Inhoud: Eén zwembad, filterpomp, reparatieplakker
Contenido: Uma piscina, bomba de filtrado, parche de reparación
Inhoud: Et bassin, filtrerpumpe, en reparationslap
Conteúdo: Uma piscina, bomba de filtraagem, remendo de reparação
ΠΕΡΙΧΟΜΕΝΑ: ΜΙΑ ΠΙΣΙΝΑ, ΑΝΤΙΑΛΤΑ ΦΙΛΤΡΟΥ, ΕΠΙΡΑΜΜΑ ΕΠΙΣΚΕΥΗΣ
В комплект входят: Один бассейн, фильтрующий насос, ремонтная заплатка
Innhald: Et basseng, filterpumpe, reparasjonslapp
Innehåll: En pool, filterpump, lägningslapp
Sisältö: Yksiallas, suodatinpumppu, korjauspaikka

1. 2. 3.

10'

220-240V~, 40W

CE TÜV Rheinland GS

Maapöytälinen ulma-allassetti
Sopava nadzemný plavecký bazén
Nadzemny zestaw basenu
Földszintes fejtálcázómedence-készlet
Virš zemės surenkamas baseinas
Komplet s samostojecim bazenom
Zemip özerine kurulan yüzme havuzu kiti
KIT de piscina superior ao solo
KIT ΠΙΣΙΝΑΣ ΕΠΙΦΑΝΕΙΑΣ
Наземный плавательный бассейн в комплекте
Sada nadzemního bazénu
Svømmebassingsæt til bruk over bakken
Utstrusting for pool ovan mark

Contents: One pool, filter pump, repair patch
Contenus: Une piscine, une pompe de filtration, une rustine
Inhalt: Ein Pool, eine Filterpumpe, Reparaturflicken
Contenuto: Una piscina, una pompa a filtro, toppa di riparazione
Inhoud: Eén zwembad, filterpomp, reparatieplakker
Contenido: Uma piscina, bomba de filtrado, parche de reparación
Inhoud: Et bassin, filtrerpumpe, en reparationslap
Conteúdo: Uma piscina, bomba de filtraagem, remendo de reparação
ΠΕΡΙΧΟΜΕΝΑ: ΜΙΑ ΠΙΣΙΝΑ, ΑΝΤΙΑΛΤΑ ΦΙΛΤΡΟΥ, ΕΠΙΡΑΜΜΑ ΕΠΙΣΚΕΥΗΣ
В комплект входят: Один бассейн, фильтрующий насос, ремонтная заплатка
Innhald: Et basseng, filterpumpe, reparasjonslapp
Innehåll: En pool, filterpump, lägningslapp
Sisältö: Yksiallas, suodatinpumppu, korjauspaikka

1. 2. 3.

10'

220-240V~, 40W

CE TÜV Rheinland GS

1. 2. 3.

10'

220-240V~, 40W

CE TÜV Rheinland GS

220-240V~, 40W

CE TÜV Rheinland GS

220-240V~, 40W

CE TÜV Rheinland GS

1. 2. 3.

10'

220-240V~, 40W

CE TÜV Rheinland GS

220-240V~, 40W

CE TÜV Rheinland GS

220-240V~, 40W

CE TÜV Rheinland GS

220-240V~, 40W

CE TÜV Rheinland GS