## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources	ULATION (EU) 2019/2	2015 with regard to ener	gy labelling of light	
Supplier's name or trade mark: vidaxl				
Supplier's address: Thomas Yang, Mary Kingsleystraat 1 5928SK Venlo The Netherlands				
Model identifier: 0720LBZ06				
Type of light source:				
Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	N/A			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
_	Product para		T	
Parameter	Value	Parameter .	Value	
	General product p			
Energy consumption in or mode (kWh/1000 h), rounde up to the nearest integer		Energy efficiency class	G	
Useful luminous flux (фuse), ir dicating if it refers to the flux is a sphere (360°), in a wide con (120°) or in a narrow cone (90°)	n Sphere (360°) e	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 000	
On-mode power (P <sub>on</sub> ), expressed in W	8,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in Nand rounded to the second decimal	V	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	87	
Outer dimen- Height	40	Spectral power dis-	See image	
sions without Width	600	tribution in the range 250 nm to 800	in last page	
separate con- trol gear, light- ing control	103	nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,460 0,408
Parameters for LED and OLED lig	ght sources:		
R9 colour rendering index value	14	Survival factor	0,99
the lumen maintenance factor	0,98		
Parameters for LED and OLED m	ains light sources:		
displacement factor (cos φ1)	0,95	Colour consistency in McAdam ellipses	2
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,0

(a)'-': not applicable; (b)'-': not applicable;

