## **Product Information Sheet**

imal

ing

Outer dimen-

sions without

separate con-

trol gear, light-

control

Height

Width

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Sumplier's name or trade marks, vidayl					
Supplier's name or trade mark: vidaxl Supplier's address: vidaXL, Mary Kingsleystraat 1 5928SK Venlo The Netherlands					
					Model identifier: 2023BZL0200
Type of light source:					
Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	NA				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
	Product para	imeters			
Parameter	Value	Parameter	Value		
	General product	parameters:			
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	1	Energy efficiency class	G		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	70 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 500		
On-mode power (P <sub>on</sub> ), ex- pressed in W	1,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or	80		

7

5

5

the range of CRI-values that can be set

Spectral power dis-

range 250 nm to 800

nm, at full-load

in

tribution

See image

in last page

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,481	
		nates (x and y)	0,420	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	8	Survival factor	0,90	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;

