Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

commission D sources	ELEGATED REGUI	-ATION (EU) 2019/2	2015 with regard to ener	gy labelling of light
Supplier's name	e or trade mark:	vidaxl		
Supplier's addre	ess: Thomas Yang	g, Mary Kingsleystra	aat 1 5928SK Venlo The	Netherlands
Model identifie	r: 2068LAH01			
Type of light so	urce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		NA		
(or other electric interface)				
Mains or non-mains:		NMLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance light source:		No		
Anti-glare shield:		No	Dimmable:	No
		Product para		1
Parameter		Value	Parameter	Value
		General product		T
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		1	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		50 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P _{on}), expressed in W		1,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82
Outer dimen-	Height	50	Spectral power dis-	See image
sions without separate con-	Width	10	tribution in the range 250 nm to 800	in last page
trol gear, light- ing control	Depth	10	nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,431			
		nates (x and y)	0,400			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	4	Survival factor	1,00			
the lumen maintenance factor	0,95					

(a)'-': not applicable; (b)'-': not applicable;

